



DIGITAL TYRE PRESSURE GAUGE

01071

SPECIFICATION

The Draper Tools policy of continuous improvement determines the right to change specification without notice.

PRESSURE RANGE:

PSI	2 – 100
BAR.....	0.15 – 7
KPA.....	15 – 700
KG/CM ²	0.15 – 7
POWER	2 X 3V AG13 (LR44) BATTERIES

DISPLAY:..... LCD

Self calibrating - +/- 1%

Low power consumption auto shut off.

IMPORTANT

Always be sure to follow manufacturer’s recommended pressure ratings.

Always check pressure when tyres are cold.

No serviceable parts or adjustments can be made. (Battery should be replaced by competent persons only).

To clean, use a soft damp cloth. Do not immerse in or spray water, other liquids or abrasive cleaners on the gauge.

OPERATION AND USE

Press the “ON” button. Wait for 0.00 psi, 0.00bar 0kPa or 0.00 kg/cm² display.

Place the gauge nozzle onto your tyre valve.

Ensure a good seal exists between the nozzle and the valve by pressing firmly, checking that no hissing sound of escaping air can be heard.

Wait for one beep, then remove the gauge nozzle from valve and read the pressure reading on the display.

To switch between psi, bar, kPa and kg/cm² depress then release the “ON” button.

This unit will switch off automatically if not used but if you wish to manually switch off – simply depress and hold the “ON” button until the LCD display is extinguished.

DISPOSAL OF TOOLS

At the end of the machine’s working life, or when it can no longer be repaired, ensure that it is disposed of according to national regulations.

Contact your local authority for details of collection schemes in your area.

In all circumstances:

- Do not dispose of power tools with domestic waste.
- Do not incinerate.
- Do not abandon in the environment.



Helpline: +44 (0) 23 8049 4344 Sales Desk: +44 (0) 23 8049 4333 General Enquiries: +44 (0) 23 8026 6355
internet: drapertools.com email: sales@drapertools.com

Draper Tools Limited

UK: Hursley Road, Chandler’s Ford, Eastleigh, Hampshire. SO53 1YF. U.K.

EU: Oude Graaf 8 6002 NL Weert (NL)

SQTL1121