



HEAVY DUTY ADHESIVE

41918

EN

Original Instructions
Version 1
April 2025

Read this leaflet in full before using this product and retain it for future use.

Intended Use

A fast acting and high strength adhesive for use where good initial strength and fast development of full bonding is required. Suitable for use on glass, wood, rubber, metal, some hard plastics and most lightweight materials such as paper, card and textiles.

NOT suitable for use on polystyrene and polyethylene/polypropylene.

NOT recommended for use where the temperature will regularly exceed 100°C.

Any other application beyond the conditions established for use will be considered misuse. Draper Tools accepts no responsibility for improper use of this product.

Direction for Use

1. Shake the can well before use.
2. Ensure all surfaces are clean, dry and free from grease.
3. Apply a thin uniform coat from a distance of 20 – 30cm.
 - **Lightweight materials** – apply to only one surface.
 - **Heavier materials** – apply to both surfaces and leave for a minimum of 30 seconds before firmly bonding together.
4. Position the two pieces of material accurately before bonding together.
 - It will take between 6 – 8 hours to cure and for full bonding to occur.
 - Once bonded together it will be difficult to separate the materials.

Important: After spraying invert the can. Then spray for 2-3 seconds to clear the spray nozzle and valve.



Helpline: +44 (0) 23 8049 4344 Sales Desk: +44 (0) 23 8049 4333 General Enquiries: +44 (0) 23 8026 6355
Internet: drapertools.com Email: sales@drapertools.com

Draper Tools Limited, Hursley Road, Chandler's Ford, Eastleigh, Hampshire. SO53 1YF UK.
Delta International, Delta International BV, Oude Graaf 8, 6002 NL, Weert, Netherlands.

0425