## MATERIAL SAFETY DATA SHEET

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

18650 Lithium ion cell,1500mAh. 3.7V.

APPLICATIONS:

For Stock No. 19403 4V MULTI-FUNCTION SCREWDRIVER

MANUFACTURER

Draper Tools Ltd

**ADDRESS** 

Hursley Road Chandlers Ford Eastleigh

Eastleigh Hampshire SO53 1YF

Draper Helpline +44 (0) 2380 494344 Opening hours 8:30-17:00 Monday – Friday.

## 2. HAZARDS IDENTIFICATION

Lithium ion cells are not hazardous when used according to the instructions of the manufacturer under normal conditions. In case of abuse, there is a risk of rupture, fire, heat, or leakage of internal components, which could release hazardous materials.

#### SYMPTOMS OF EXPOSURE

Skin contact

No effect under routine handling and use.

Skin absorption

No effect under routine handling and use.

Eye contact

No effect under routine handling and use.

Inhalation

No effect under routine handling and use.

#### REPORTED AS CARCINOGEN

Not applicable

## 3. COMPOSITION INFORMATION

| INGREDIENTS          | %   | CAS NUMBER |
|----------------------|-----|------------|
| Lithium Nickel Oxide | 16  | 12031-65-1 |
| Lithium cobaltate    | 6.4 | 12190-79-3 |

| ate: 2021. Jan. 5          | %           | CAS NUMBER |
|----------------------------|-------------|------------|
| INGREDIENTS                | <del></del> | <u> </u>   |
| lithium manganate          | 9.6         | 12057-17-9 |
| Anode active material      | 17          | 7782-42-5  |
| Graphite                   |             |            |
| LiPF6                      | .2          | 21324-40-3 |
| EC                         | 4           | 96-49-1    |
| EMC                        | 7           | 623-53-0   |
| PC                         | 1           | 108-32-7   |
| Nickel                     | 2           | 7440-02-0  |
| Aluminum                   | 12          | 7429-90-5  |
| Copper                     | 8           | 7440-50-8  |
| Carbon                     | 2           | 7440-44-0  |
| Polyvinylidene             | 4           | 24937-79-9 |
| fluoride                   |             | 24931-19-9 |
| Polyethylene               | 3           | 9002-88-4  |
| Polyethylene terephthalate | 6           | 25038-59-9 |

#### **FURTHER INFORMATION**

For information purposes:

(\*) Main ingredients: Lithium hexafluorophosphate, organic carbonates

Because of the cell structure the dangerous ingredients will not be available if used properly.

During charge process a lithium graphite intercalation phase is formed.

Mercury content: Hg < 0.1mg/kg Cadmium content: Cd < 1mg/kg Lead content: Pb< 10mg/kg

## 4. FIRST-AID MEASURES

INHALATION, EYE CONTACT, and SKIN CONTACT: Not a health hazard.

#### **INGESTION**

If swallowed, obtain medical attention immediately.

If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended.

#### INHALATION

Leave area immediately and seek medical attention.

#### **EYE CONTACT**

Rinse eyes with water for 15 minutes and seek medical attention.

SKIN CONTACT

Wash area thoroughly with soap and water and seek medical attention.

#### INGESTION

Drink milk/water and induce vomiting; seek medical attention.

### 5. FIRE FIGHTING MEASURES

**GENERAL HAZARD** 

Cell is not flammable but internal organic material will burn if the cell is incinerated.

Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

## EXTINGUSHING MEDIA

Use extinguishing media suitable for the materials that are burning.

## SPECIAL FIREFIGHTING INSTRUCTIONS

If possible, remove cell(s) from fire fighting area.

If heated above 120 °C, cell(s) can explode/vent.

FIREFIGHTING EQUIPMENT

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### ON LAND

Place material into suitable containers and call local fire/police department.

#### IN WATER

If possible, remove from water and call local fire/police department.

## 7. HANDLING AND STORAGE

#### HANDLING

No special protective clothing required for handling individual cells.

#### **STORAGE**

Store in cool, dry place.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

3 of 7

Keep away from heat and open flame.

PERSONAL PROTECTION

Store in a cool dry place.

Respirator:

Not required during normal operations, event of a fire.

SCBA required in the

Eye/face protection:

Gloves:

Foot protection:

Not required beyond safety practices of employer.

Not required for handling of cells.

Steel toed shoes recommended for large container handling.

# 9. PHYSICAL AND CHEMICAL PROPETIES

Appearance Form: Solid Color: Various Odor: Odourless

important health, safety and environmental information

Test method

| pHValue              | N/A       |
|----------------------|-----------|
| Flash point          | N/A       |
| Lower explosion      | N/A       |
| Vapor pressure       | N/A       |
| Density              | N/A       |
| Water solubility     | insoluble |
| Ignition temperature | N/A       |

REACTIVITY

None

**INCOMPATIBILITIES** 

None during normal operation.

Avoid exposure to heat, open flame, and corrosives.

## HAZARDOUS DECOMPOSITION PRODUCTS

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

CONDITIONS TO AVOID

Avoid exposure to heat and open flame.

Do not puncture, crush or incinerate.

## 11. TOXICOLOGICAL INFORMATION

Cells are not hazardous when used properly. In case of fire or leakage combustion and decomposition products may cause irritation and toxicity to skin, eye and respiratory systems.

Toxicity data of some substance is listed:

Hydrogen fluoride:

Extremely toxic, May be fatal if inhaled or ingested. Readily absorbed through the skin contact may be fatal. Possible mutagen. LCLO: 50 ppm/30m (human beings). LC50: 1276 ppm/1h (rats).

Carbon and graphite:

Slightly hazards in case of skin contact (irritant), ingestion, inhalation, which will cause chronic damage to upper respiratory tract and cardiovascular system.

Copper:

File No./Rev.: MSDS-163/C

Dust may cause respiratory irritation.

LD50: 3.5 mg kg-1(mouse).

## 12. ECOLOGICAL INFORMATION

Some materials within the cell are bioaccumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

## 13. DISPOSAL INFORMATION

Recommended methods for safe and environmentally preferred disposal:

Product (waste from residues)

Do not throw out a used battery cell. Recycle it through the recycling company.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

RCRA Waste Code:

No regulated

Dispose of according to all federal, state, and local regulations.

## 14. TRANSPORTATION INFORMATION

With regard to transport, the following regulations are cited and considered:

The International Civil Aviation Organization (ICAO) Technical Instructions, Packing Instruction 965, Section IB,

The International Air Transport Association (IATA) Dangerous Goods Regulations, Packing Instruction 965, Section IB (61th Edition)

The International Maritime Dangerous Goods (IMDG) Code (2018 Edition),

US Harzardous Materials Regulations 49 CFR(Code of Federal Regulations)

Sections 173-185 Lithium batterie and cells,

The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries, Rev.6,

The article is nor restricted to IMO IMDG code according to special provision 188(Amdt.39-18)(2018 Edition)

Hazard Classification: The goods are complied with the requirements of Section IB of Packing Instructions 965 of 61st DGR Manual of IATA(2020 edition), Special provision 188 of IMDG CODE(Amdt. 39-18)(2018 Edition), including the passing of the UN38.3 test.

Our products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 – T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Testes and Criteria.

Test results of the UN Recommendation on the Transport of Dangerous Goods

| Manu | al of Test and Criteria(38.3 Lithium battery) | Test results | Remark |
|------|---|--------------|--------|
| No.  | Test items                                    |              |        |
| T1   | Altitude Simulation                           | Pass         |        |
| T2   | Thermal Test                                  | Pass         |        |
| ТЗ   | Vibration                                     | Pass         |        |

| ssuec | Date: 2021. Jan. 9     |      |                                       |
|-------|------------------------|------|---------------------------------------|
| T4    | Shock                  | Pass |                                       |
| T5    | External Short Circuit | Pass |                                       |
| T6    | Impact                 | Pass |                                       |
| T7    | Overcharge             | Pass | For pack and single cell battery only |
| T8    | Forced Discharge       | Pass |                                       |

UN code:3480,3481

## 15. REGULATORY INFORMATION

For shipping regulations see section 14.

## 16. OTHER INFORMATION

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide.

The information and recommendations set forth are made in good faith and believed to be accurate as of makes no warranty, expressed or implied, the date of preparation.

with respect to this information and disclaims all liabilities from reliance on it