



# SAFETY DATA SHEET

## 1. Identification of the Substance/Mixture and of the Company/Undertaking

### 1.1 Product Identifier:

Trade name:  
21667 Draper 2kg CO2 Fire Extinguisher

### 1.2 Relevant Identified Uses:

Fire extinguisher for use on electrical and flammable liquid fires (Class B).

### 1.3 Details of the Supplier of the Safety Data Sheet:

**Company name:** Draper Tools Ltd  
**Address:** Hursley Road, Chandler's Ford  
Eastleigh, Hampshire SO53 1YF  
**Telephone:** +44 (0) 23 80266355  
**Email:** sales@drapertools.com  
**Contact person:** Customer Service  
**Website:** www.drapertools.com

### 1.4 Emergency Telephone Number:

+44 (0) 23 80266355 (not 24hrs)

## 2. Hazards Identification

**Hazard Classification:** Class 2 Sub Class 2

### Hazard Identification:

Liquefied gas. Contact with product may cause cold burns or frost bite.

**Hazard Class and Category Code - Regulation EC 1272/2008 (CLP)**

### Physical hazards:

Gases under pressure - Compressed gas - Warning (H280)

**Classification EC 67/548 or EC 1999/45/CE**

Not included in Annex VI.

Not classified as dangerous preparation/substance.

No EC labelling required.

### Label Element

Labelling Regulation EC 1272/2008 (CLP)

### Propellant hazard pictograms



**Hazard pictograms code:** GHS04

**Signal word:** Warning

### Hazard statements:

H280 - Contains gas under pressure; may explode if heated

### Precautionary statements:

Storage: P403 - Store in a well-ventilated place

Labelling: EC 67/548 or EC 1999/45

Symbol(s): None

R Phrase(s): None

S Phrase(s): None

Asphyxiant in high concentrations

### Other hazards:

Contact with liquid may cause cold burns/frostbite.

In high concentrations CO2 causes rapid circulatory insufficiency even at normal levels of oxygen concentration.

Symptoms are headache, nausea and vomiting, which may lead to unconsciousness and death.

## 3. Composition/Information on Ingredients

**Substance Name:** Carbon Dioxide

**CAS No.:** 124-38-9

**EC-No.:** 204-696-9

**Extinguisher Content Mass (kg):** 2kg

Contains no other components or impurities which will influence the classification of the product.

## 4. First Aid Measures

---

### **Inhalation:**

Call doctor if victim is unconscious, move to uncontaminated area. Perform Cardiopulmonary Resuscitation (CPR) or assisted respiration if required. Low concentrations of CO<sub>2</sub> cause increased respiration and headache. Remove victim to uncontaminated area to breathe fresh air. Keep warm and quiet. Continued treatment should be symptomatic and supportive.

### **Eye Contact:**

Immediately flush eyes with plenty of water for 15 minutes whilst holding lids open. If redness, itching or burning occurs get medical attention.

### **Skin Contact:**

Wash material off skin with copious amounts of water and soap for at least 15 minutes. If redness, itching or burning occurs get medical attention. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

**Ingestion:** Not applicable.

### **Acute Overexposure:**

Carbon Dioxide is non-toxic at normal temperature and pressure. By diluting the oxygen concentration in air below the level necessary to support life, it can act as an asphyxiant. Effects of oxygen deficiency are (at % of Oxygen in air): 12-16%: breathing and pulse rate increased, muscular coordination slightly disturbed; 10-14%: emotional upset, normal fatigue, disturbed respiration; 6- 10% nausea and vomiting, collapse or loss of consciousness; below 6%: convulsive movements, possible respiratory collapse and death.

### **Chronic Overexposure:**

Long term exposure to carbon dioxide has no known health effects. Prolonged exposure to an oxygen deficient atmosphere (below 18% oxygen in air) may affect the heart and nervous system.

## 5. Fire Fighting Measures

---

### **Suitable Extinguishing Media:**

This is an extinguishing agent - use water spray or fog.

**Hazards from Combustion:** None.

### **Products: PPE for Fire Fighters.**

Rescuers should not enter oxygen depleted room without the use of self contained full face breathing equipment. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

**Hazchem Code:** 2TE

### **Specific Hazards:**

Exposure to fire may cause containers to rupture or explode. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.

## 6. Accidental Release Measures

---

### **Personal precautions, protective equipment and emergency procedures:**

Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when asphyxiating gases may be released.

### **Emergency Procedures:**

Evacuate area and ventilate. Do not enter area where high concentrations may exist without appropriate protective equipment.

### **Methods and Materials for Containment and Clean Up:**

Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (ground free from frost).

## 7. Handling and Storage

---

### **General:**

Protect cylinders from physical damage; do not drag, roll, slide or drop. Handle in well-ventilated areas. The maintenance and repair of the fire extinguisher must be carried out by qualified personnel in accordance with relevant regulations.

Never use direct flame or electrical heating devices to raise the pressure of the container.

Do not remove or deface labels provided by the supplier for the identification of the contents of the extinguisher.

### **Safe Storage:**

Store in cool, dry, well ventilated areas out of direct sunlight and away from heat and ignition sources. Do not expose any cylinder

part to temperatures above 55°C, store upright on a level floor, secure in position and protect from damage. Full cylinders stored separately from empties.

Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion.

Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

## 8. Exposure Controls/Personal Protection

### Personal Protection:

Ensure adequate ventilation. Protect eyes, face and skin.

### National Exposure Controls:

Carbon Dioxide ES-TWA 5,000 ppm & Carbon Dioxide ES-STEL 30,000 ppm

### Carbide dioxide (124-38-9)

#### OEL (Occupational Exposure Limits)

EU	TWA IOELV (EU) 8 h [mg/m <sup>3</sup> ]	9000 mg/m <sup>3</sup>
	TWA IOELV (EU) 8 h [ppm]	5000 ppm
United Kingdom	WEL - LTEL - UK [mg/m <sup>3</sup> ]	9150 mg/m <sup>3</sup>
	WEL - LTEL - UK [ppm]	5000 ppm
	WEL - STEL - UK [mg/m <sup>3</sup> ]	27400 mg/m <sup>3</sup>
	WEL - STEL - UK [ppm]	15000 ppm
Ireland	OEL (IE)- (8 hour reference period) [mg/m <sup>3</sup> ]	9000 mg/m <sup>3</sup>
	OEL (IE)- (8 hour reference period) [ppm]	5000 ppm
	OEL (IE)- (15 min reference period) [mg/m <sup>3</sup> ]	27000 mg/m <sup>3</sup>
	OEL (IE)- (15 min reference period) [ppm]	15000 ppm
	Notes (IE)	IOELV

### Appropriate Engineering Controls:

Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. CO2 detectors should be used when CO2 may be released.

### Individual Protection Measures:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

## 9. Physical and Chemical Properties

<b>Colour:</b>	Colourless
<b>Odour:</b>	Odourless
<b>Relative density, gas (air=1):</b>	1.52
<b>Relative density liquid (air=1):</b>	0.82
<b>Solubility in water [mg/l]:</b>	2000
<b>Melting Point:</b>	-78.5°C

<b>Boiling Point:</b>	-56.6°C
<b>Flammability Range:</b>	Non flammable
<b>Critical Temperature:</b>	30°C
<b>Vapour Pressure [20° C]:</b>	57.3 bar
<b>Other Data:</b>	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## 10. Stability and Reactivity

<b>Chemical Stability:</b>	Stable under normal conditions of handling and use.
<b>Incompatible Materials:</b>	Not applicable.

<b>Hazardous Reactions:</b>	None
<b>Conditions of Avoid:</b>	None
<b>Hazardous Decomposition Products:</b>	None

## 11. Toxicological Information

### Acute Toxicology:

Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, O2). CO2 has been shown to enhance the production of carboxy - or

met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems.

### Eye Contact:

The liquid form of this material can produce chilling sensations and discomfort and also frostbite.

## 11. Toxicological Information

---

### Skin Contact:

Evaporation of liquid from skin can produce chilling sensations. Frostbite can occur. Avoid carbon dioxide snow.

### Inhalation:

Carbon dioxide is an asphyxiate. Effects of oxygen deficiency (below 6%) are as follows: convulsive movements, possible respiratory collapse and death.

### Ingestion:

Not a likely route of entry.

### Acute Overexposure:

Contact can produce chilling sensations, light headedness, giddiness, shortness of breath, muscular tremors and weakness, and acrocyanosis. Also unconsciousness or even death.

### Chronic Overexposure:

Prolonged exposure to an oxygen deficient atmosphere (below 18% oxygen) may affect the heart and nervous system.

## 12. Ecological Information

---

**Eco Toxicity:** Not available.

**Mobility:** Not available.

**Bio Accumulative Potential:** Not available.

**Persistence and Degradability:** Not available.

**Environmental Fate (Exposure):** Not available.

## 13. Disposal Considerations

---

### General:

Dispose of in compliance with local authority regulations. It can be discharged to atmosphere in a well ventilated place, this should be avoided in large quantities. Where accumulation could be dangerous do not discharge. The gas cylinders are

refillable. If the cylinder should be placed out of service, ask the manufacturer/ supplier about recovery/recycling information.

### Special Precautions of Landfill or Incineration

Do not incinerate.

## 14. Transport Information

---

### UN No.:

1044 FIRE EXTINGUISHERS with compressed or liquefied gas

### Class and Subsidiary Risk:

D. G. Class 2.2 Non-flammable, non-toxic gases

**Special Precautions for User:** None

### UN Proper Shipping Name:

FIRE EXTINGUISHER Packing Group III 2TE

**Packing Group:**



**Hazchem Code:**

## 15. Regulatory Information

---

### Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

#### EU Regulations

Restrictions on Use: No one.  
Seveso regulations 96/82/CE: Not included.

### National Regulations

Ensure all national/local regulations are observed.

### Chemical Safety Assessment:

This product is not necessary to carry out a chemical safety assessment (CSA).

## 16. Other Information

---

### Training Advice:

After use indoors, ventilate thoroughly.  
Do not breathe the gas.  
Keep container in a well-ventilated place.

### List of full text of the indications section 3.

H280 - Contains gas under pressure; may explode if heated.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.