

SAFETY DATA SHEET

Issue Date: 16/10/2025 Version: 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: Alkaline Battery (AA)

Applications: For: COB LED Work Light (94507)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Not for recharge

1.3. Details of the supplier of the safety data sheet

Draper Tools Ltd

Hursley Road, Chandlers Ford, Eastleigh

Hampshire SO53 1YF

United Kingdom

www.drapertools.com

1.4. Emergency telephone number

Draper Helpline +44 (0) 2380 494344

Opening hours 8:30-17:00 Monday – Friday.

SECTION 2: Hazards identification

Hazards Identification:

The battery is not restricted to IATA DGR according to special provision A123 and is not restricted to IMDG CODE according to special provision 304.

Emergency Overview:

Avoid contact or inhalation the internal materials emit toxic fumes under fire conditions.

SECTION 3: Composition/information on ingredients

Product name: Alkaline Battery

Ingredient	Concentration	CAS No.
Graphite	2~6%	7782-42-5
Manganese Dioxide	30~45%	1313-13-9
Potassium Hydroxide	4~8%	1310-58-3
Zinc	12~25%	7440-66-6
Steel	20%	7439-89-6
Brass	3%	12597-71-6
Water	11%	7732-18-5

SECTION 4: First aid measures

Skin Exposure:

If the internal battery materials of an opened battery cell come into contact with the skin, immediately flush with plenty of water.

Eye Exposure:

In case of contact with eyes, flush with water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

Inhalation Exposure:

In case of exposure to nickel fumes or dusts occurs, leave immediately to fresh air and seek medical attention.

Oral Exposure:

If swallow, do not induce vomiting. Seek immediate medical attention.

SECTION 5: Firefighting measures

Extinguishing Media:

Suitable: Dry chemical, carbon dioxide and appropriate foam.

Firefighting:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Specific hazards: Emit toxic fumes under fire conditions.

SECTION 6: Accidental release measure

Procedure of Personal Precaution:

Exercise appropriate precautions to minimize direct contact with skin and eyes.

Methods for Cleaning up:

Sweep up with spade, place into a dry, clean, lidded container for disposal. Avoid raising dust. Ventilate area and wash spill site after material pickup is complete.

SECTION 7: Handling and storage

Handling:

Wear appropriate protective clothing and safety gloves. Avoid contact and inhalation the internal materials.

Keep away from ignition sources, heat and flame.

Incompatibilities: strong oxidizing agents, corrosives and foods. Such batteries must be packed in inner packaging in such a manner as to effectively prevent short circuits. No smoking at working site.

Storage:

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Store in a tightly closed container.

Incompatibilities: strong oxidizing agents, corrosives and foods.

SECTION 8: Exposure controls/personal protection

Engineering controls:

Use ventilation equipment if available. Safety shower and eye bath.

Personal Protective Equipment:

Respiratory System: Wear protective mask if needed.

Eyes: Wear safety goggles if needed.

Clothing: Wear appropriate protective clothing.

Hand: Wear safety gloves.

Other Protection:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION 9: Physical and chemical properties

Appearance:	Cylinder
Odour:	Odourless
Melting Point / °C	> 350°C
Solubility:	Partial soluble in water
Stability:	Stable under normal temperatures and pressures.
Conditions to Avoid:	Avoid exposure to heat and open flame. Do not puncture, crush or incinerate. Prevent short circuits. Prevent movement which could lead to short circuits. Do not attempt to recharge this battery.
Materials to Avoid:	Strong oxidizing agents, corrosives.
Hazardous Polymerization:	Will not occur.

Hazardous Decomposition Products: When exposed to extreme heat/fire, batteries may rupture leaking corrosive material and/or emit toxic fumes. Burning batteries may emit toxic fumes of zinc oxide and manganese oxide.

SECTION 10: Stability and reactivity

Stability:

Stable under normal temperatures and pressures.

Conditions to Avoid:

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate. Prevent short circuits.

Prevent movement which could lead to short circuits. Do not attempt to recharge this battery.

Materials to Avoid:

Strong oxidizing agents, corrosives.

Hazardous Polymerization:

Will not occur.

Hazardous Decomposition Products:

When exposed to extreme heat/fire, batteries may rupture leaking corrosive material and/or emit toxic fumes.

Burning batteries may emit toxic fumes of zinc oxide and manganese oxide.

SECTION 11: Toxicological information

Toxicity Data:

Not available.

Irritation Date:

The internal battery materials may cause irritation to eyes and skin.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Appropriate Method of Disposal of Substance:

Dispose of in accordance with all applicable federal, state and local regulations.

SECTION 14: Transport information

IATA: Not restricted to IATA DGR according to special provision A123.

IMO: Not restricted to IMDG CODE according to special provision 304.

SECTION 15: Regulatory information

Manganese Dioxide Battery is unregulated for purpose of transportation by *U.S. Department of Transportation (DOT)*, *International Civil Aviation Administration (ICAA)*, *International Air Transport Association (IATA)* and *the International Maritime Dangerous Goods regulations (IMDG)*.

The only DOT requirement for shipping these batteries is Special Provision 130 which states: "Batteries, dry, are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals)."

The only requirements for shipping these batteries by ICAA and IATA is Special Provision A123 which states: "An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short-circuit(e.g.in the case of batteries, by the effective insulation of exposed

terminals: or in the case of equipment, by disconnection of the battery and protection of exposed terminals) is forbidden from transportation.”

The International Maritime Dangerous Goods Code (IMDG) regulate them for ocean transportation under Special Provision 304 which says: “Batteries, dry, containing corrosive electrolyte which will not flow out of the battery if the battery case is cracked are not subject to the provisions of this Code provided the batteries are securely packed and protected against short-circuits. Examples of such batteries are alkaline-manganese, zinc-carbon, nickel metal hydride and nickel-cadmium batteries.”

The requirements for shipping these batteries, in all modes of transportation, are that they be separated from each other to prevent short-circuits and to prevent movement that could lead to short-circuits. Products must also be packed in strong packaging that can withstand the rigors normal to transportation.

SECTION 16: Other information

Issue Date: 16/10/2025 Version: 2

This Safety Data Sheet contains health, safety and environment information, and was written by reflecting current technology. This data is not a guarantee for the product's character or quality and should be used only as a reference in relation to safe use of the product.

***End of SDS ***